
METRIX PRIMUS, BATTERIEBETRIEB

TOUCH FREE ELECTRONIC FAUCET, STAINLESS STEEL

SPECIAL FEATURES	•••••••••••••••••••••••••••••••••••••••
Activated by Infrared sensor	
For cold and premixed water	
Drastically reduces water consumption	
Helps protect against cross contamination	
Sensor settings adjustable by optional remote con	trol
Easy Installation	
External solenoid valve	
Stainless Steel AISI 316	
	• • • • • • • • • • • • • • • • • • • •
TECHNICAL DETAILS	
Operating water pressure 0.5-8.0 bar (7-116 PSI), for a pressure reducing valve	or water pressure greater than 8.0 bar use
Max. water temperature 70°C (158°F)	
Water saving options 6 LPM/1.58 GPM; 4 LPM/1 G 1.3 LPM/0.35 GPM	PM; 3 LPM/0.8 GPM; 1.89 LPM/ 0.5 GPM;
Preset sensor range 120mm, adjustable with optio	nal remote control
Powered by 9V Battery	
Preset security time 90 seconds, can be reduced w	ith optional remote control
Default hygiene flush every 24 hours for 30 second	ls, adjustable from 12-72 hours
MODELS AVAILABLE	Code Number
METRIX PRIMUS, Battery	1993850
METRIX PRIMUS, Transformer	1993853
Remote control	1002597
Matching soap dispenser	1991810





199 38 50

ADVANTAGES













ADA DESIGNED

Daimlerstraße 2, D-93133 Burglengenfeld, Germany Tel. +49 (0) 9471 / 600 93-0 Fax +49 (0) 9471 / 88 55 www.benkiser.de info@benkiser.de

BEAKIJER